

MA2 ACTUATING AXES SELF-CENTERING SOLID AIR CHUCK FIXTURES


兩軸自動求心氣壓夾盤

兩軸自動求心氣壓夾盤專供中心機及各式工作台面的加工而設計，在X,Y兩軸間同時夾持任何異形工件具快速自定工件中心之功能。具3大特色：

- 1.氣缸防銹處理：**在潮溼及工作環境較差的情況，氣缸內部經防銹處理，不會生銹或卡死。
- 2.防塵裝置：**在工作台上的銼銑工作、切屑及冷卻液不易進入夾盤內部，確保夾盤的使用壽命及精度。
- 3.多邊夾持、自定中心：**有別於虎鉗的單一軸向夾持，兩軸自動求心氣壓夾盤分別在X,Y兩軸向分割成兩組夾持動作，且同時自定工件中心，能快速準確的固定工件，在任一軸向銼削均能達到穩固的效果。



尺寸圖 > Dimensions



專利產品
Patent Protected

2 actuating axes self-centering solid air chuck fixtures is great for machining center. Two pairs of jaws clamp one after another to assure a workpiece to be locked completely.

- 1.Rust-proof for Pneumatic Cylinder:**
Inside wall of cylinder being rustproof treated; cylinder can work under wet or high moisture circumstances without rusty or seized trouble.
- 2.Dusts-proof and Waterproof:**
Dust-proof and Waterproof structure prevents work-chips and coolant water from entering into inside of chuck cylinder to maintain its accuracy and lead to longer service life.
- 3.4-jaw Clamping and Self-centering:**
4-jaw clamping are steadier for machining. Two pairs of jaws are moved independently to assure complete lock and self-centering.

應用實例 > Operation Example

快速、準確、自動化
Speed, Accurate, Automatic

兩段分割夾持，自定中心
4-jaws clamping and self-center



規格表 > Specifications

型式/規格 MODEL / SPEC.	A	B	D	E	F	G	H	I	J	K	L	M	N
MA-06	224	175	20	130	170	40	73	20	12	31	18	ø11	ø202
MA-08	265	210	22	154	196	42	95	25	14	35	18	ø11	ø243
MA-10	315	250	25	176	222	46	110	30	16	40	18	ø13	ø285
型式/規格 MODEL / SPEC.	O			P			Q			A 活塞面積 推力側 Push Side		Piston Area (cm ²) 拉力側 Pull Side	
MA-06	M10x1.5P(PCD ø202)			4-M8x1.25P(PCD ø124)			4-M8x1.25P(PCD ø156)			127		108	
MA-08	M10x1.5P(PCD ø243)			4-M10x1.5P(PCD ø140)			4-M10x1.5P(PCD ø186)			184		157	
MA-10	M12x1.75P(PCD ø285)			4-M10x1.5P(PCD ø176)			4-M10x1.5P(PCD ø224)			270		239	
型式/規格 MODEL / SPEC.	B 活塞面積 推力側 Push Side		Piston Area (cm ²) 拉力側 Pull Side		柱塞行程 Plunger Stroke (mm)	爪行程 (直徑) Jaw Stroke (Diameter) (mm)	空壓夾持力 Gripping Force At Air Pressure 7kgf/cm ² (0.7Mpa) kgf (KN)			淨重 Weight (kg)	夾持範圍 Gripping Range		
MA-06	122		117		12	5.5	4500 (44)			24.8	ø25~ø175		
MA-08	176		169		16	7.4	6400 (63)			41.3	ø30~ø210		
MA-10	254		241		19	8.8	9500 (93)			65.6	ø35~ø250		